



ASSEMBLY AND INSTALLATION INSTRUCTIONS

H0270

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. Read and save these instructions.


Hardware Package (included):



Installation Steps

Turn off the power at fuse or circuit box.

1. Attach the mounting strap unit (A) to the outlet box by using two mounting screws (B).
Note: The depth of threaded pipe on the mounting strap unit may need to be adjusted to properly fit the fixture.
2. Secure the two rods onto the fixture by using the threaded pipes. Determine length of chain (F) needed to achieve desired fixture height. (To remove excess chain section, use pliers to bend link open.) Weave the fixture wires through the chain (F) and canopy. Connect the two chains (F) to the canopy and fixture loops with four quick links (E).
3. Pull out the source wires from the outlet box. Make wire connections using wire connectors (C) as follows:
 - Connect the smooth-coated wire (marked) from the fixture to the black wire (hot) from the power source.
 - Connect the ribbed-coated wire (unmarked) from the fixture to the white wire (neutral) from the power source.
 - Attach the fixture ground wire (bare wire) to the mounting strap unit (A) with the green ground screw. Then, depending on local code, connect it to the house ground wire with a wire connector (C).Carefully put all of the wires back into the outlet box.



4. Attach the canopy to the mounting strap unit (A) by aligning and inserting the threaded pipe from the mounting strap unit (A) into the center hole on the canopy, then secure the canopy with the finial (D).
5. Install 3 x 60W medium base bulbs (not included). See relamping label at socket area or packaging for maximum wattage allowed.

Turn on the power at fuse or circuit box.

The following parts are available for re-order if damaged or missing.

Spare Parts List:

Mounting Strap Unit (A)	Mounting Screw (B)	Wire Connector (C)	Finial (D)	Quick Link (E)	Chain (F)

↓
Assembly Kit
6522MM (1 SET)

